

SIZE TABLES

Wood and Aluminum-Clad Exteriors
Standard Awning



Vent Units

	(451) (432)	(552) (533)	(603) (584)	(654) (635)	(756) (737)
Opening	1' 5 3/4"	1' 9 3/4"	1' 11 3/4"	2' 1 3/4"	2' 5 3/4"
Frame	1' 5"	1' 9"	1' 11"	2' 1"	2' 5"

Vent and Fixed Units

	(832) (813)	(908) (889)	(1 060) (1 041)	(1 213) (1 194)	(1 365) (1 346)	(1 518) (1 499)
Opening	2' 8 3/4"	2' 11 3/4"	3' 5 3/4"	3' 11 3/4"	4' 5 3/4"	4' 11 3/4"
Frame	2' 8"	2' 11"	3' 5"	3' 11"	4' 5"	4' 11"

Fixed Units

	(908) (889)	(1 060) (1 041)	(1 213) (1 194)	(1 365) (1 346)	(1 518) (1 499)	(1 670) (1 651)	(1 822) (1 803)	(1 873) (1 854)
Opening	2' 11 3/4"	3' 5 3/4"	3' 11 3/4"	4' 5 3/4"	4' 11 3/4"	5' 5 3/4"	5' 11 3/4"	6' 1 3/4"
Frame	2' 11"	3' 5"	3' 11"	4' 5"	4' 11"	5' 5"	5' 11"	6' 1"

Special Size Frame Dimensions*

		MAXIMUM
VENT	1'1-3/4" W x 1'1-3/4" H (350 x 350)	4'5" W x 2'5" H (1 346 x 737)
FIXED	10" W x 10" H (254 x 254)	12" W x 12" H (3 658 x 3 658)

* Available within size range shown. Contact your local Pella representative for availability of Triple-Glazing on larger custom unit sizes.

Keep frame dimensions to the nearest 1/4" increment. Frame height cannot exceed frame width on special size vent units.

Opening Dimensions

CLAD EXTERIOR UNITS: Dimensions shown in tables are rough opening dimensions.

WOOD EXTERIOR UNITS: Use frame dimension plus dimensions below. This dimension includes the use of standard 1-1/8" wood subsill.

FRAME	MASONRY			
Brickmould	Width	Height	Width	Height
STD	+ 3/4"	+ 1-7/8"	+ 3-1/8"	+ 3-1/8"
3-1/2"	+ 3/4"	+ 1-7/8"	+ 6-3/8"	+ 4-3/4"


For clad and wood units with HurricaneShield® impact-resistant glass, see the product installation instructions or refer to local building code requirements.

Not to scale.

Ⓢ Fixed Units only

Traditional grille patterns shown. Refer to Clad/Wood Overview Section for additional patterns and profiles.

Contact your local Pella representative for the availability of custom sizes smaller or larger than the parameters shown, Triple-Glazing or other custom fixed shapes.



SIZE TABLES

Wood and Aluminum-Clad Exteriors Large Awning



Vent Units

	(908) (889)	(1 060) (1 041)	(1 213) (1 194)	(1 365) (1 346)	(1 518) (1 499)
Opening	2' 11 3/4"	3' 5 3/4"	3' 11 3/4"	4' 5 3/4"	4' 11 3/4"
Frame	2' 11"	3' 5"	3' 11"	4' 5"	4' 11"
(908) (889)					
(1 060) (1 041)					
(1 213) (1 194)					
(1 365) (1 346)					
(1 518) (1 499)					

Special Size Frame Dimensions*

		MAXIMUM
VENT	1'9" W x 1'5" H (889 x 889)	6'1" W x 6'1" H (1 854 x 1 854)

* Available within size range shown.

Keep frame dimensions to the nearest 1/4" increment.

Opening Dimensions

CLAD EXTERIOR UNITS: Dimensions shown in tables are rough opening dimensions.

WOOD EXTERIOR UNITS: Use frame dimension plus dimensions below. This dimension includes the use of standard 1-1/8" wood subsill.

FRAME	MASONRY			
Brickmould	Width	Height	Width	Height
STD	+ 3/4"	+1-7/8"	+ 3-1/8"	+ 3-1/8"
3-1/2"	+ 3/4"	+1-7/8"	+ 6-3/8"	+ 4-3/4"

For clad and wood units with HurricaneShield® impact-resistant glass, see the product installation instructions or refer to local building code requirements.

Not to scale.

Traditional grille patterns shown. Refer to Clad/Wood Overview Section for additional patterns and profiles.

All units are available as fixed in the Casement section.

Contact your local Pella representative for the availability of custom sizes smaller or larger than the parameters shown, Triple-Glazing or other custom fixed shapes.