



OUT-SWING DOOR

SIZE TABLES

Aluminum-Clad Exterior

6' 7-1/2"



6' 7 1/2" Single Doors and Sidelight

Opening	1' 6 3/4" (476)	2' 2 1/8" (664)	2' 6 3/4" (781)	2' 10 1/4" (870)	3' 0 3/4" (933)	3' 2 5/8" (981)
Frame	1' 6" (457)	2' 1 3/8" (645)	2' 6" (762)	2' 9 1/2" (851)	3' 0" (914)	3' 1 7/8" (962)

  

(2 032) (2 019)	6' 8" 6' 7 1/2"						
		SIDELIGHT 1880	LEFT 2680	LEFT 3080	LEFT 3480	LEFT 3680	LEFT 3880

6' 7 1/2" Double-Swing Doors

Opening	4' 2 3/4" (1 289)	5' 0" (1 524)	5' 7" (1 702)	6' 0" (1 829)	6' 3 3/4" (1 924)
Frame	4' 2" (1 270)	4' 11 1/4" (1 505)	5' 6 1/4" (1 682)	5' 11 1/4" (1 810)	6' 3" (1 905)

  

(2 032) (2 019)	6' 8" 6' 7 1/2"					
		ACTIVE-PASSIVE 5080	ACTIVE-PASSIVE 6080	ACTIVE-PASSIVE 6780	ACTIVE-PASSIVE 7280	ACTIVE-PASSIVE 7580

Not to scale.

Traditional grille patterns shown. Refer to Clad/Wood Overview section for additional patterns and profiles.

All doors and sidelights are glazed with tempered glass.

For windows and patio doors with HurricaneShield® impact-resistant glass, see product instructions or refer to local building code requirements.

Single doors - Left-hand shown. Right-hand and fixed are available.

Double-swing doors - Active-Passive shown. Passive-Active also available.

**For Wood Units Only:**

To determine masonry dimensions when using Pella 1-7/8" brickmould, add 1-5/8" to frame height and 3-1/8" to frame width. When using Pella 3-1/2" brickmould, add 6-3/8" to frame width and 3-1/4" to frame height.



OUT-SWING DOOR

**SIZE TABLES**  
Aluminum-Clad Exterior  
6'10" and 7'2"



6' 10" Single Doors and Sidelight

Opening	1' 6 3/4" (476)	2' 2 1/8" (664)	2' 6 3/4" (781)	2' 10 1/4" (870)	3' 0 3/4" (933)	3' 2 5/8" (981)
Frame	1' 6" (457)	2' 1 3/8" (645)	2' 6" (762)	2' 9 1/2" (851)	3' 0" (914)	3' 1 7/8" (962)

6' 10" Double-Swing Doors

Opening	4' 2 3/4" (1 289)	5' 0" (1 524)	5' 7" (1 702)	6' 0" (1 829)	6' 3 3/4" (1 924)
Frame	4' 2" (1 270)	4' 11 1/4" (1 505)	5' 6 1/4" (1 682)	5' 11 1/4" (1 810)	6' 3" (1 905)

7' 2" Single Doors and Sidelight

Opening	1' 6 3/4" (476)	2' 2 1/8" (664)	2' 6 3/4" (781)	2' 10 1/4" (870)	3' 0 3/4" (933)	3' 2 5/8" (981)
Frame	1' 6" (457)	2' 1 3/8" (645)	2' 6" (762)	2' 9 1/2" (851)	3' 0" (914)	3' 1 7/8" (962)

7' 2" Double-Swing Doors

Opening	4' 2 3/4" (1 289)	5' 0" (1 524)	5' 7" (1 702)	6' 0" (1 829)	6' 3 3/4" (1 924)
Frame	4' 2" (1 270)	4' 11 1/4" (1 505)	5' 6 1/4" (1 682)	5' 11 1/4" (1 810)	6' 3" (1 905)

Not to scale.

Traditional grille patterns shown. Refer to Clad/Wood Overview section for additional patterns and profiles.

All doors and sidelights are glazed with tempered glass.

For windows and patio doors with HurricaneShield® impact-resistant glass, see product instructions or refer to local building code requirements.

Single doors - Left-hand shown. Right-hand and fixed are available.

Double-swing doors - Active-Passive shown. Passive-Active also available.

**For Wood Units Only:**

To determine masonry dimensions when using Pella 1-7/8" brickmould, add 1-5/8" to frame height and 3-1/8" to frame width. When using Pella 3-1/2" brickmould, add 6-3/8" to frame width and 3-1/4" to frame height.



OUT-SWING DOOR

**SIZE TABLES**  
Aluminum-Clad Exterior  
8'0" and 10'0"



8' 0" Single Doors and Sidelight

Opening	1' 6 3/4" (476)	2' 2 1/8" (664)	2' 6 3/4" (781)	2' 10 1/4" (870)	3' 0 3/4" (933)	3' 2 5/8" (981)
Frame	1' 6" (457)	2' 1 3/8" (645)	2' 6" (762)	2' 9 1/2" (851)	3' 0" (914)	3' 1 7/8" (962)

8' 0" Double-Swing Doors

Opening	4' 2 3/4" (1 289)	5' 0" (1 524)	5' 7" (1 702)	6' 0" (1 829)	6' 3 3/4" (1 924)
Frame	4' 2" (1 270)	4' 11 1/4" (1 505)	5' 6 1/4" (1 682)	5' 11 1/4" (1 810)	6' 3" (1 905)

10' 0" Single Doors

Opening	2' 2 1/8" (664)	2' 6 3/4" (781)	2' 10 1/4" (870)	3' 0 3/4" (933)	3' 2 5/8" (981)
Frame	2' 1 3/8" (645)	2' 6" (762)	2' 9 1/2" (851)	3' 0" (914)	3' 1 7/8" (962)

10' 0" Double-Swing Doors

Opening	4' 2 3/4" (1 289)	5' 0" (1 524)	5' 7" (1 702)	6' 0" (1 829)	6' 3 3/4" (1 924)
Frame	4' 2" (1 270)	4' 11 1/4" (1 505)	5' 6 1/4" (1 682)	5' 11 1/4" (1 810)	6' 3" (1 905)

Not to scale.

Traditional grille patterns shown. Refer to Clad/Wood Overview section for additional patterns and profiles.

All doors and sidelights are glazed with tempered glass.

For windows and patio doors with HurricaneShield® impact-resistant glass, see product instructions or refer to local building code requirements.

Single doors - Left-hand shown. Right-hand and fixed are available.

Double-swing doors - Active-Passive shown. Passive-Active also available.

**For Wood Units Only:**

To determine masonry dimensions when using Pella 1-7/8" brickmould, add 1-5/8" to frame height and 3-1/8" to frame width. When using Pella 3-1/2" brickmould, add 6-3/8" to frame width and 3-1/4" to frame height.



OUT-SWING DOOR

SIZE TABLES

Aluminum-Clad Exterior  
Transoms



Wide Stile Transoms for Single Doors

		Opening	2' 2 1/8" (664)	2' 6 3/4" (781)	2' 10 1/4" (870)	3' 0 3/4" (933)	3' 2 5/8" (981)
		Frame	2' 1 3/8" (645)	2' 6" (762)	2' 9 1/2" (851)	3' 0" (914)	3' 1 7/8" (962)
(451) (654)	1' 5"						
	1' 5 3/4"						
(635)	2' 1"						
	2' 1 3/4"						

Standard Stile Transoms for Single Doors

(451) (654)	1' 5"					
	1' 5 3/4"					
(635)	2' 1"					
	2' 1 3/4"					

Fixed Frame Direct Sets for Single Doors

(451) (654)	1' 5"					
	1' 5 3/4"					
(635)	2' 1"					
	2' 1 3/4"					

Wide Stile Transoms for Double-Swing Doors

		Opening	4' 2 3/4" (1 289)	5' 0" (1 524)	5' 7" (1 702)	6' 0" (1 829)	6' 3 3/4" (1 924)
		Frame	4' 2" (1 270)	4' 11 1/4" (1 505)	5' 6 1/4" (1 682)	5' 11 1/4" (1 810)	6' 3" (1 905)
(451) (654)	1' 5"						
	1' 5 3/4"						
(635)	2' 1"						
	2' 1 3/4"						

Standard Stile Transoms for Double-Swing Doors

(451) (654)	1' 5"					
	1' 5 3/4"					
(635)	2' 1"					
	2' 1 3/4"					

Fixed Frame Direct Sets for Double-Swing Doors

(451) (654)	1' 5"					
	1' 5 3/4"					
(635)	2' 1"					
	2' 1 3/4"					

Not to scale.

Tempered glass is standard.

Traditional grille patterns shown. Refer to Clad/Wood Overview section for additional patterns and profiles.