




## PRODUCT SELECTION GUIDE

Size and Performance Data

Sound Transmission Class and Outdoor-Indoor Transmission Class



AWNING

Awning	BLOCK FRAME	INTEGRAL NAILING FIN
<b>SIZES</b>		
Standard Vent/Fixed	●	●
Standard Fixed Companion Sizes	●	●
Special Sizes	●	●
<b>PERFORMANCE<sub>1</sub></b>		
Meets or Exceeds AAMA/WDMA Ratings	AP-LC50 Hallmark Certified	AP-LC50 Hallmark Certified
Air Infiltration (cfm/ft <sup>2</sup> of frame @ 1.57 psf wind pressure)	0.05	0.05
Water Resistance	7.5 psf	7.5 psf
Design Pressure	50 psf	50 psf
<b>OTHER PERFORMANCE CRITERIA</b>		
Forced Entry Resistance Level (Minimum Security Grade) <sub>2</sub>	40	40
Maximum Operating Force (lb) Initiate Motion/Maintain Motion	15/6	15/6

Large Awning	BLOCK FRAME	INTEGRAL NAILING FIN
<b>SIZES</b>		
Standard Vent/Fixed	●	●
Special Sizes	●	●
<b>PERFORMANCE<sub>1</sub></b>		
Meets or Exceeds AAMA/WDMA Ratings	AP-LC30 - AP-LC50 Hallmark Certified	AP-LC30 - AP-LC50 Hallmark Certified
Air Infiltration (cfm/ft <sup>2</sup> of frame @ 1.57 psf wind pressure)	0.05	0.05
Water Resistance	7.5 psf	7.5 psf
Design Pressure	30 - 50 psf	30 - 50 psf
<b>OTHER PERFORMANCE CRITERIA</b>		
Forced Entry Resistance Level (Minimum Security Grade) <sub>2</sub>	40	40
Maximum Operating Force (lb) Initiate Motion/Maintain Motion	6/3	6/3

### SOUND TRANSMISSION CLASS AND OUTDOOR-INDOOR TRANSMISSION CLASS

Product	Frame Size Tested <sub>3</sub>	Glazing System			STC Rating	OITC Rating
		Overall Glazing Thickness	Exterior Glass Thickness	Interior Glass Thickness		
AWNING VENT	59-1/2" x 23-1/2"	11/16"	2.5mm	2.5mm	25	22
	59-1/2" x 23-1/2"	11/16"	3mm	5mm	32	28
	59-1/2" x 23-1/2"	11/16"	3mm	6mm Laminated	32	28
AWNING FIXED	59-1/2" x 47-1/2"	11/16"	3mm	3mm	27	23
	59-1/2" x 47-1/2"	11/16"	3mm	5mm	31	26
	59-1/2" x 47-1/2"	11/16"	3mm	6mm Laminated	32	27
	59-1/2" x 47-1/2"	11/16"	4mm	7mm Laminated	33	29

(1) See Design Data pages in this section for specific product performance class and grade values.


(2) The higher the level, the greater the product's ability to resist forced entry.

(3) ASTM E 1425 defines standard sizes for acoustical testing. Ratings achieved at that size are representative of all sizes of the same configuration.



# PRODUCT SELECTION GUIDE

## Features and Options



AWNING

	BLOCK FRAME	INTEGRAL NAILING FIN
<b>GLAZING</b>		
<b>Glazing Type</b>		
Dual-pane Insulating Glass	S	S
<b>Insulated Glass Options / Low-E Types</b>		
Clear Insulating Glass (no Low-E coating)	S	S
Advanced Low-E Insulating Glass	O	O
SunDefense™ Low-E Insulating Glass	O	O
AdvancedComfort Low-E Insulating Glass	O	O
NaturalSun Low-E Insulating Glass	O	O
<b>Additional Glass Options</b>		
Annealed Glass	S	S
Tempered Glass	O	O
Noise reduction glass (3/5mm, 4/6mm combinations)	O	O
Noise Reduction laminated glass (non-impact)	O	O
Tinted glass (Bronze, Gray, Green) Advanced Low-E	O	O
Obscure Glass <sub>1</sub>	O	O
<b>Gas Fill / High Altitude</b>		
Argon	S	S
High Altitude	O	O
High Altitude with argon	O	O
<b>EXTERIOR / INTERIOR</b>		
Powder-Coat White	S	S
Powder-Coat Tan, Brown, Black, or Morning Sky Gray	O	O
Dual-color (All Exterior Colors with White interior)	O	-
<b>HARDWARE</b>		
Match interior finish	S	S
Satin Nickel, Bright Brass or Oil-Rubbed Bronze	O	O
<b>SASH LOCKS</b>		
SureLock® System	S	S
Unison Lock System <sub>2</sub>	S	S
<b>SCREENS</b>		
Conventional Black Fiberglass	O	O
InView™ screens	O	O
<b>GRILLES</b>		
<b>Grilles-Between-the-Glass</b>		
Traditional, Prairie, Top Row and Custom - Equally Divided	O	O

S = Standard; O = Optional; (-) = Not available

(1) Contact your local Pella sales representative for current offering.

(2) Unit size determines availability.