

# DESIGN DATA






## Integral Mullion



FIXED FRAME DIRECT SET

L (IN)	W (IN)	DESIGN PRESSURE (PSF) <sub>1</sub>		
		20	25	30
48	48	A	A	A
48	54	A	A	A
48	60	A	A	A
48	66	A	A	A
48	72	A	A	A
48	75	A	A	A
54	36	A	A	A
54	42	A	A	A
54	48	A	A	A
54	54	A	A	A
54	60	A	A	A
54	66	A	A	B
60	24	A	A	A
60	30	A	A	A
60	36	A	A	A
60	42	A	A	A
60	48	A	A	B
60	54	A	B	B
60	60	A	B	B
66	18	A	A	A
66	24	A	A	A
66	30	A	A	A
66	36	A	A	B
66	42	A	B	B
66	48	A	B	B
66	54	B	B	B
72	12	A	A	A
72	18	A	A	A
72	24	A	A	A
72	30	A	A	B
72	36	A	B	B
72	42	B	B	B
72	48	B	B	B
72	50	B	B	B
78	12	A	A	A
78	18	A	A	A
78	24	A	B	B
78	30	B	B	B
78	36	B	B	B
78	42	B	B	B
78	46	B	B	B
84	12	A	A	A
84	18	A	A	B
84	24	B	B	B
84	30	B	B	B
84	36	B	B	B
84	42	B	B	B

L (IN)	W (IN)	DESIGN PRESSURE (PSF) <sub>1</sub>		
		20	25	30
90	12	A	A	A
90	18	A	B	B
90	24	B	B	B
90	30	B	B	B
90	36	B	B	B
90	40	B	B	-
96	12	A	A	B
96	18	B	B	B
96	24	B	B	B
96	30	B	B	B
96	36	B	B	-
96	37	B	B	-
102	12	A	B	B
102	18	B	B	B
102	24	B	B	B
102	30	B	B	-
102	35	B	-	-
108	12	B	B	B
108	18	B	B	B
108	24	B	B	-
108	30	B	-	-
108	33	B	-	-



(-) = Not Available

Composite units are not AAMA/WDMA performance certified. Pella Impervia composites are engineered to meet performance class and grade shown.

See the Combinations section to determine if reinforcing mullion is needed when mulling multiple composites into a combination.

(1) Maximum performance when glazed with the appropriate glass thickness.