Six (6) Pin Uncut Keylock Cylinder
Special Instructions

These instructions apply to:

Pella® Lifestyle Series Dual-Pane & Triple-Pane 04/2019-Current
Architect Series® Hinged Doors 1992-Current
Architect Series® Sliding Doors 2002-Current
Designer Series® Hinged and Sliding Doors 1992-03/2019
Pella® 450 Series Hinged and Sliding Doors 1992-03/2019



Z-Clip

For hinged door applications: Use the enclosed Z-clip.

For sliding door applications: Do not use the spacer included in the handle hardware pack.

All locks are keyed to a 111111 position.

These keys can be installed and used to secure the door during the construction process, but the keylock cylinder **MUST BE RE-KEYED BY A LOCKSMITH** prior to the customer taking occupancy. The locksmith can use the enclosed key to cut the new pattern or use a Schlage C-K style key.

Please make sure to leave the locksmith contact information with the customer so they can contact if needed.

Six (6) Pin Uncut Keylock Cylinder
Special Instructions

These instructions apply to:

Pella® Lifestyle Series Dual-Pane & Triple-Pane 04/2019-Current
Architect Series® Hinged Doors 1992-Current
Architect Series® Sliding Doors 2002-Current
Designer Series® Hinged and Sliding Doors 1992-03/2019
Pella® 450 Series Hinged and Sliding Doors 1992-03/2019



Z-Clip

For hinged door applications: Use the enclosed Z-clip.

For sliding door applications: Do not use the spacer included in the handle hardware pack.

All locks are keyed to a 111111 position.

These keys can be installed and used to secure the door during the construction process, but the keylock cylinder **MUST BE RE-KEYED BY A LOCKSMITH** prior to the customer taking occupancy. The locksmith can use the enclosed key to cut the new pattern or use a Schlage C-K style key.

Please make sure to leave the locksmith contact information with the customer so they can contact if needed.

© 2009 Pella Corporation Rev. 03/15/2019 **Page 1 of 1** GIF - 000000795-1 Part Number: 80X90000