



# Test Report Information

## Pella® Reserve™ and Architect Series® Traditional

**Note:** These charts are to be used for documentation of independent testing compliance of published Performance Class & Grade shown in the Design and Performance data tables. Use test report information where the unit width and height in the table below are equal or greater in size to the unit being specified. Contact your local Pella sales representative for copies of full test reports.

(1) Maximum performance for single units when glazed with the appropriate glass.

Product Type	Brand	Frame	Configuration	Performance Type	Glazing	Width	Height	Positive Design Pressure	Negative Design Pressure	Performance Class & Grade <sub>1</sub>	Hallmark Certified	FPAS# (Florida Product Approval System)	TDI# (Texas Department of Insurance)	Test Report# (Independent Report)	Canadian Performance (Pella CSA Rating Claim)
Awning Jamb Operator	Pella Reserve / Architect Series	Aluminum Clad Wood	Vent	Standard	Annealed	29	29	+50	-50	CW-PG50	411-H-915	11284	WIN1581	ESP033465P.2	A3
Awning Jamb Operator	Pella Reserve / Architect Series	Aluminum Clad Wood	Vent	Standard	Annealed	53	29	+50	-50	CW-PG50	411-H-915	11284	WIN1581	ESP033465P.2	A3
Awning Sill Operator	Pella Reserve / Architect Series	Aluminum Clad Wood	Vent	Standard	Annealed	59	73	+30	-30	LC-PG30	411-H-1228	14345	WIN1581	ESP028341P.11	A3
Awning Sill Operator	Pella Reserve / Architect Series	Aluminum Clad Wood	Vent	Standard	Annealed	59	59	+40	-40	LC-PG40	411-H-1228	14345	WIN1581	ESP028341P.12	A3
Awning - Precision Fit	Pella Reserve / Architect Series	Aluminum Clad Wood	Fixed	Standard	Annealed	59	35	+50	-50	CW-PG50	411-H-1132	14130.2	WIN1391	TCT003412P.6	Fixed
Awning - Precision Fit	Pella Reserve / Architect Series	Aluminum Clad Wood	Vent	Standard	Annealed	53	35	+50	-50	R-PG50	411-H-1134	14129.2	—	TCT003412P.8	A3
Awning - Precision Fit	Pella Reserve / Architect Series	Aluminum Clad Wood	Vent	Standard	Annealed	53	29	+50	-50	R-PG50	411-H-1134	14130.2	WIN1393	TCT003412P.8	A3
Casement	Pella Reserve / Architect Series	Aluminum Clad Wood	Vent	Standard	Annealed	35	73	+50	-50	CW-PG50	411-H-905	11282	WIN1576	ESP028341P.7	A3
Casement	Pella Reserve / Architect Series	Aluminum Clad Wood	Vent	Standard	Annealed	41	77	+40	-40	LC-PG40	411-H-905	11282	WIN1576	ESP028341P.3	A3
Casement	Pella Reserve / Architect Series	Aluminum Clad Wood	Fixed	Standard	Annealed	35	73	+50	-50	CW-PG50	411-H-912	11277	WIN1582	ESP028341P.6	Fixed
Casement	Pella Reserve / Architect Series	Aluminum Clad Wood	Fixed	Standard	Annealed	120	86	+50	-50	CW-PG50	411-H-938	11277	WIN1582	ESP028341P.16	Fixed
Casement	Pella Reserve / Architect Series	Aluminum Clad Wood	Fixed	Standard	Annealed	61	96	+50	-50	CW-PG50	411-H-938	11277	WIN1582	ESP028341P.17	Fixed



# Test Report Information

## Pella® Reserve™ and Architect Series® Traditional

**Note:** These charts are to be used for documentation of independent testing compliance of published Performance Class & Grade shown in the Design and Performance data tables. Use test report information where the unit width and height in the table below are equal or greater in size to the unit being specified. Contact your local Pella sales representative for copies of full test reports.

(1) Maximum performance for single units when glazed with the appropriate glass.

Product Type	Brand	Frame	Configuration	Performance Type	Glazing	Width	Height	Positive Design Pressure	Negative Design Pressure	Performance Class & Grade <sub>1</sub>	Hallmark Certified	FPAS# (Florida Product Approval System)	TDI# (Texas Department of Insurance)	Test Report# (Independent Report)	Canadian Performance (Pella CSA Rating Claim)
Casement	Pella Reserve / Architect Series	Aluminum Clad Wood	Fixed	Standard	Annealed	60	73	+50	-50	CW-PG50	411-H-938	11277	WIN1582	ESP028341P.8	Fixed
Casement - Shapes and Custom Sash	Pella Reserve / Architect Series	Aluminum Clad Wood	Fixed	Standard	11/16" & 1" IG up to 36 Sq. Ft	87	65	+50	-50	CW-PG50	411-H-1136	11277.4	0	ESP027559P.13	Fixed
Casement - Shapes and Custom Sash	Pella Reserve / Architect Series	Aluminum Clad Wood	Fixed	Standard	11/16" & 1" IG up to 36 Sq. Ft	79	96	+40	-40	CW-PG40	411-H-1136	11277.4	0	ESP027559P.8	Fixed
Casement - Shapes and Custom Sash	Pella Reserve / Architect Series	Aluminum Clad Wood	Fixed	Standard	11/16" & 1" IG up to 36 Sq. Ft	110	53	+50	-50	LC-PG50	411-H-1137	11277.4	0	ESP027559P.7	Fixed
Casement - Shapes and Custom Sash	Pella Reserve / Architect Series	Aluminum Clad Wood	Vent	Standard	11/16" & 1" IG up to 36 Sq. Ft	29	96	+50	-50	LC-PG50	411-H-1186	11282.8	0	ESP027559P.5	A3
Casement - Shapes and Custom Sash	Pella Reserve / Architect Series	Aluminum Clad Wood	Vent	Standard	11/16" & 1" IG up to 36 Sq. Ft	37.5	75	+50	-50	LC-PG50	411-H-1186	11282.8	0	ESP027559P.1	A3
Casement - Shapes and Custom Sash	Pella Reserve / Architect Series	Aluminum Clad Wood	Vent	Standard	11/16" & 1" IG up to 36 Sq. Ft	41	68.25	+50	-50	LC-PG50	411-H-1186	11282.8	0	ESP027559P.2	A3
Casement - Precision Fit	Pella Reserve / Architect Series	Aluminum Clad Wood	Vent	Standard	Annealed	35	73	+50	-50	R-PG50	411-H-1127	14128.2	WIN1394	TCT003412P.1	A3
Casement - Precision Fit	Pella Reserve / Architect Series	Aluminum Clad Wood	Vent w/ Side Pivot Hardware	Standard	Annealed	35	73	+50	-50	R-PG50	411-H-1127	14128.2	WIN1394	TCT003412P.3	A3
Casement - Precision Fit	Pella Reserve / Architect Series	Aluminum Clad Wood	Fixed	Standard	Annealed	35	73	+50	-50	CW-PG50	411-H-1131	14129.2	WIN1395	TCT003412P.2	Fixed
Casement - Precision Fit	Pella Reserve / Architect Series	Aluminum Clad Wood	Fixed	Standard	Annealed	59	73	+50	-50	CW-PG50	411-H-1131	14129.2	WIN1392	TCT003412P.4rev	Fixed
Hung - Double	Pella Reserve / Architect Series	Aluminum Clad Wood	Vent w/ 2 Locks	Standard	11/16" 2.5mm Annealed IG	48	84	+40	-40	CW-PG40	411-H-1213	14341	WIN-1090	ESP017480P.2	A3



# Test Report Information

## Pella® Reserve™ and Architect Series® Traditional

**Note:** These charts are to be used for documentation of independent testing compliance of published Performance Class & Grade shown in the Design and Performance data tables. Use test report information where the unit width and height in the table below are equal or greater in size to the unit being specified. Contact your local Pella sales representative for copies of full test reports.

(1) Maximum performance for single units when glazed with the appropriate glass.

Product Type	Brand	Frame	Configuration	Performance Type	Glazing	Width	Height	Positive Design Pressure	Negative Design Pressure	Performance Class & Grade <sub>1</sub>	Hallmark Certified	FPAS# (Florida Product Approval System)	TDI# (Texas Department of Insurance)	Test Report# (Independent Report)	Canadian Performance (Pella CSA Rating Claim)
Hung - Double	Pella Reserve / Architect Series	Aluminum Clad Wood	Vent w/ 2 Locks	Standard	11/16" 2.5mm Annealed IG	48	77	+45	-45	CW-PG45	411-H-1213	14341	WIN-1090	ESP017480P.4	A3
Hung - Double	Pella Reserve / Architect Series	Aluminum Clad Wood	Vent w/ 2 Locks	Standard	11/16" 2.5mm Annealed IG	45	65	+50	-50	CW-PG50	411-H-1213	14341	WIN-1090	ESP017480P.6	A3
Hung - Double	Pella Reserve / Architect Series	Aluminum Clad Wood	Vent w/ 2 Locks	Standard	11/16" 2.5mm Annealed IG	41	71	+50	-50	CW-PG50	411-H-1213	14341	WIN-1090	ESP017480P.7	A3
Hung - Double	Pella Reserve / Architect Series	Aluminum Clad Wood	Vent w/ 2 Locks	Standard	11/16" 2.5mm Annealed IG	37	77	+50	-50	CW-PG50	411-H-1213	14341	WIN-1090	ESP017480P.3	A3
Hung - Double - Precision Fit	Pella Reserve / Architect Series	Aluminum Clad Wood	Vent w/ 2 Locks	Standard	11/16" 2.5mm Annealed IG	48	84.735	+40	-40	CW-PG40	411-H-1219	14343	WIN-1089	ESP017942P.2	A3
Hung - Double - Precision Fit	Pella Reserve / Architect Series	Aluminum Clad Wood	Vent w/ 2 Locks	Standard	11/16" 2.5mm Annealed IG	41.5	72.234	+50	-50	CW-PG50	411-H-1219	14343	WIN-1089	ESP017942P.3	A3
Monumental Hung - Double	Pella Reserve / Architect Series	Aluminum Clad Wood	Vent w/ 2 Locks	Standard	13/16" 3mm Annealed IG	54	96	+50	-50	CW-PG50	411-H-1478	17769.2	NA	ESP018981P.1	NA
Monumental Hung - Double	Pella Reserve / Architect Series	Aluminum Clad Wood	Vent w/ 2 Locks	Standard	13/16" 3mm Heat Strengthened IG	72	144	+30	-30	LC-PG30	411-H-1478	NA	NA	ESP018981P.5	NA
Monumental Hung - Double	Pella Reserve / Architect Series	Aluminum Clad Wood	Vent w/ 2 Locks	Standard	13/16" 4mm Annealed IG	60	120	+30	-30	CW-PG30	411-H-1478	NA	NA	ESP018981P.4	NA
Patio Door - In-Swing	Pella Reserve / Architect Series	Aluminum Clad Wood	AP or PA	Standard	Tempered	75	95.5	+55	-70	LC-PG55	411-H-1164	14293	DR635	TCT003560P.1rev2	A3
Patio Door - In-Swing	Pella Reserve / Architect Series	Aluminum Clad Wood	AP or PA	Standard	Tempered	75	119.5	+40	-40	LC-PG40	411-H-1164	14293	DR635	TCT003560P.4rev2	A3
Patio Door - In-Swing	Pella Reserve / Architect Series	Aluminum Clad Wood	Fixed	Standard	Tempered	38	119.5	+55	-55	CW-PG55	411-H-1164	14293	DR635	TCT003560P.7rev3	Fixed



**Test Report Information**  
**Pella® Reserve™ and**  
**Architect Series® Traditional**

**Note:** These charts are to be used for documentation of independent testing compliance of published Performance Class & Grade shown in the Design and Performance data tables. Use test report information where the unit width and height in the table below are equal or greater in size to the unit being specified. Contact your local Pella sales representative for copies of full test reports.

(1) Maximum performance for single units when glazed with the appropriate glass.

Product Type	Brand	Frame	Configuration	Performance Type	Glazing	Width	Height	Positive Design Pressure	Negative Design Pressure	Performance Class & Grade <sub>1</sub>	Hallmark Certified	FPAS# (Florida Product Approval System)	TDI# (Texas Department of Insurance)	Test Report# (Independent Report)	Canadian Performance (Pella CSA Rating Claim)
Patio Door - In-Swing	Pella Reserve / Architect Series	Aluminum Clad Wood	AF or FA	Standard	Tempered	75	95.5	+55	-55	LC-PG55	411-H-1436	14293	DR635	ESP012181P.14	A2
Patio Door - Out-Swing	Pella Reserve / Architect Series	Aluminum Clad Wood	AP or PA	Standard	Tempered	75	119.5	+55	-55	LC-PG55	411-H-1188	14302	DR-548	TCT003663P.1	A3
Patio Door - Out-Swing	Pella Reserve / Architect Series	Aluminum Clad Wood	Fixed	Standard	Tempered	48	119.5	+70	-70	LC-PG70	411-H-1188	14302	DR-548	TCT003663P.9	Fixed
Patio Door - Out-Swing	Pella Reserve / Architect Series	Aluminum Clad Wood	Fixed	Standard	Tempered	38	119.5	+70	-85	LC-PG70	411-H-1188	14302	DR-548	TCT003663P.2	Fixed
Patio Door - Out-Swing	Pella Reserve / Architect Series	Aluminum Clad Wood	AP or PA	Standard	Tempered	75	81.5	+70	-85	LC-PG70	411-H-1188	14302	DR-548	TCT003663P.3	A3
Patio Door - Out-Swing	Pella Reserve / Architect Series	Aluminum Clad Wood	AP or PA	Standard	Tempered	75	95.5	+70	-70	LC-PG70	411-H-1188	14302	DR-548	TCT003663P.6rev	A3
Patio Door - Out-Swing	Pella Reserve / Architect Series	Aluminum Clad Wood	AP or PA	Standard	Tempered	75	81.5	+70	-85	LC-PG70	411-H-1188	14302	DR-548	TCT003663P.11	A3
Sliding Door	Pella Reserve / Architect Series	Aluminum Clad Wood	Fixed	Standard	Tempered	48.788	95.5	+70	-70	LC-PG70	411-H-1490	12459	P	ESP024305P.2	A3
Sliding Door	Pella Reserve / Architect Series	Aluminum Clad Wood	OXO	Standard	Tempered	144.039	95.5	+45	-45	LC-PG45	411-H-728	12459	P	ESP024305P.8	A3,
Sliding Door	Pella Reserve / Architect Series	Aluminum Clad Wood	OX or XO	Standard	Tempered	71.25	95.5	+65	-65	LC-PG65	411-H-728	12459	P	ESP024305P.6	A3,
Sliding Door	Pella Reserve / Architect Series	Aluminum Clad Wood	OX or XO	Standard	Tempered	95.25	95.5	+60	-60	LC-PG60	411-H-729	12459	P	ESP024305P.5	A3,
Sliding Door	Pella Reserve / Architect Series	Aluminum Clad Wood	OXXO	Standard	Tempered	140.125	95.5	+40	-40	R-PG40	411-H-719	12459	—	ESP024305P.1	A3



**Test Report Information**  
**Pella® Reserve™ and**  
**Architect Series® Traditional**

**Note:** These charts are to be used for documentation of independent testing compliance of published Performance Class & Grade shown in the Design and Performance data tables. Use test report information where the unit width and height in the table below are equal or greater in size to the unit being specified. Contact your local Pella sales representative for copies of full test reports.

(1) Maximum performance for single units when glazed with the appropriate glass.

Product Type	Brand	Frame	Configuration	Performance Type	Glazing	Width	Height	Positive Design Pressure	Negative Design Pressure	Performance Class & Grade <sub>1</sub>	Hallmark Certified	FPAS# (Florida Product Approval System)	TDI# (Texas Department of Insurance)	Test Report# (Independent Report)	Canadian Performance (Pella CSA Rating Claim)
Sliding Door	Pella Reserve / Architect Series	Aluminum Clad Wood	OXXO	Standard	Tempered	188.125	95.5	+30	-30	R-PG30	411-H-719	12459	—	ESP024305P.7	A3

**Reference Sites**

[WDMA Hallmark Certification](#)

[Florida Product Approval Site](#)

[Texas Department of Insurance Site](#)

For copies of full test reports contact your local Pella Sales Representative.