



Test Report Information
Pella® Reserve™ Traditional
and Contemporary

Note: These charts are to be used for documentation of independent testing compliance of published Performance Class & Grade shown in the Design and Performance data tables. Use test report information where the unit width and height in the table below are equal or greater in size to the unit being specified. Contact your local Pella sales representative for copies of full test reports.

(1) Maximum performance for single units when glazed with the appropriate glass.

Product Type	Brand	Frame	Configuration	Performance Type	Glazing	Width	Height	Positive Design Pressure	Negative Design Pressure	Performance Class & Grade ₁	Hallmark Certified	FPAS# (Florida Product Approval System)	TDI# (Texas Department of Insurance)	Test Report# (Independent Report)	Canadian Performance (Pella CSA Rating Claim)
Awning Jamb Operator	Pella Reserve Traditional and Contemporary	Aluminum Clad Wood	Vent	Standard	Annealed	53	29	+50	-50	CW-PG50	411-H-915	11284	WIN1581	ESP028341P.15	A3
Awning Sill Operator	Pella Reserve Traditional and Contemporary	Aluminum Clad Wood	Vent	Standard	Annealed	59	73	+30	-30	LC-PG30	411-H-1228	14345	WIN1581	ESP028341P.11	A3
Awning Sill Operator	Pella Reserve Traditional and Contemporary	Aluminum Clad Wood	Vent	Standard	Annealed	59	59	+40	-40	LC-PG40	411-H-1228	14345	WIN1581	ESP028341P.12	A3
Casement	Pella Reserve Traditional and Contemporary	Aluminum Clad Wood	Vent	Standard	See Note 1	35	73	+50	-50	CW-PG50	411-H-905	31311	WIN1576	ESP028341P.7	A3
Casement	Pella Reserve Traditional and Contemporary	Aluminum Clad Wood	Vent	Standard	Annealed	41	77	+40	-40	LC-PG40	411-H-905	31311	WIN1576	ESP028341P.3	A3
Casement	Pella Reserve Traditional and Contemporary	Aluminum Clad Wood	Vent	Standard	See Note 1	35	96	+50	-50	CW-PG50	411-H-905	31311	WIN1576	ESP028341P.2	A3
Casement	Pella Reserve Traditional and Contemporary	Aluminum Clad Wood	Vent	Standard	Annealed	47	108	+30	-30	LC-PG30	411-H-905	31311	0	ESP034013P	A2
Casement	Pella Reserve Traditional and Contemporary	Aluminum Clad Wood	Fixed	Standard	See Note 1	35	73	+50	-50	CW-PG50	411-H-912	31312	WIN1582	ESP028341P.6	Fixed
Casement	Pella Reserve Traditional and Contemporary	Aluminum Clad Wood	Fixed	Standard	Tempered	120	86	+50	-50	CW-PG50	411-H-938	31312	WIN1582	ESP028341P.16	Fixed
Casement	Pella Reserve Traditional and Contemporary	Aluminum Clad Wood	Fixed	Standard	Tempered	61	96	+50	-50	CW-PG50	411-H-938	31312	WIN1582	ESP028341P.17	Fixed
Casement	Pella Reserve Traditional and Contemporary	Aluminum Clad Wood	Fixed	Standard	Annealed	60	73	+50	-50	CW-PG50	411-H-938	31312	WIN1582	ESP028341P.8	Fixed
Casement - Shapes and Custom Sash	Pella Reserve Traditional	Aluminum Clad Wood	Fixed	Standard	Annealed	87	65	+50	-50	CW-PG50	411-H-1136	11277	0	ESP027559P.13	Fixed



Test Report Information
Pella® Reserve™ Traditional
and Contemporary

Note: These charts are to be used for documentation of independent testing compliance of published Performance Class & Grade shown in the Design and Performance data tables. Use test report information where the unit width and height in the table below are equal or greater in size to the unit being specified. Contact your local Pella sales representative for copies of full test reports.

(1) Maximum performance for single units when glazed with the appropriate glass.

Product Type	Brand	Frame	Configuration	Performance Type	Glazing	Width	Height	Positive Design Pressure	Negative Design Pressure	Performance Class & Grade ₁	Hallmark Certified	FPAS# (Florida Product Approval System)	TDI# (Texas Department of Insurance)	Test Report# (Independent Report)	Canadian Performance (Pella CSA Rating Claim)
Casement - Shapes and Custom Sash	Pella Reserve Contemporary	Aluminum Clad Wood	Fixed	Standard	Annealed	60	73	+50	-50	CW-PG50	411-H-1508	31704	0	ESP028341P.18	Fixed
Casement - Shapes and Custom Sash	Pella Reserve Traditional	Aluminum Clad Wood	Fixed	Standard	Tempered	79.75	96	+40	-40	CW-PG40	411-H-1143	11277	0	ESP027559P.8	Fixed
Casement - Shapes and Custom Sash	Pella Reserve Contemporary	Aluminum Clad Wood	Fixed	Standard	Tempered	79.75	96	+50	-50	CW-PG50	411-H-1508	31704	0	ESP028341P.24	Fixed
Casement - Shapes and Custom Sash	Pella Reserve Traditional	Aluminum Clad Wood	Fixed	Standard	See Note 1	110	53	+50	-50	LC-PG50	411-H-1137	11277	0	ESP027559P.7	Fixed
Casement - Shapes and Custom Sash	Pella Reserve Contemporary	Aluminum Clad Wood	Fixed	Standard	See Note 1	110	53	+50	-50	R-PG50	411-H-1508	31704	0	ESP028341P.25	Fixed
Casement - Shapes and Custom Sash	Pella Reserve Contemporary	Aluminum Clad Wood	Vent	Standard	Annealed	29.25	96	+50	-50	R-PG50	411-H-1509	31681	0	ESP028341P.20	A3
Casement - Shapes and Custom Sash	Pella Reserve Traditional	Aluminum Clad Wood	Vent	Standard	Annealed	29.25	96	+50	-50	LC-PG50	411-H-1186	11282	0	ESP027559P.5	A3
Casement - Shapes and Custom Sash	Pella Reserve Contemporary	Aluminum Clad Wood	Vent	Standard	Annealed	37.5	75	+50	-50	R-PG50	411-H-1509	31681	0	ESP028341P.22	A2
Casement - Shapes and Custom Sash	Pella Reserve Traditional	Aluminum Clad Wood	Vent	Standard	Annealed	37.5	75	+50	-50	LC-PG50	411-H-1186	11282	0	ESP027559P.16	A2
Casement - Shapes and Custom Sash	Pella Reserve Contemporary	Aluminum Clad Wood	Vent	Standard	Annealed	41	68.25	+50	-50	R-PG50	411-H-1509	31681	0	ESP028341P.21	A3
Casement - Shapes and Custom Sash	Pella Reserve Traditional	Aluminum Clad Wood	Vent	Standard	Annealed	41	68.25	+50	-50	LC-PG50	411-H-1186	11282	0	ESP027559P.2	A3
Hung - Double	Pella Reserve Traditional	Aluminum Clad Wood	Vent w/ 2 Locks	Standard	Annealed	48	84	+40	-40	CW-PG40	411-H-1213	14341	WIN-1090	ESP038732P.2	A2



Test Report Information
Pella® Reserve™ Traditional
and Contemporary

Note: These charts are to be used for documentation of independent testing compliance of published Performance Class & Grade shown in the Design and Performance data tables. Use test report information where the unit width and height in the table below are equal or greater in size to the unit being specified. Contact your local Pella sales representative for copies of full test reports.

(1) Maximum performance for single units when glazed with the appropriate glass.

Product Type	Brand	Frame	Configuration	Performance Type	Glazing	Width	Height	Positive Design Pressure	Negative Design Pressure	Performance Class & Grade ₁	Hallmark Certified	FPAS# (Florida Product Approval System)	TDI# (Texas Department of Insurance)	Test Report# (Independent Report)	Canadian Performance (Pella CSA Rating Claim)
Hung - Double	Pella Reserve Traditional	Aluminum Clad Wood	Vent w/ 2 Locks	Standard	Annealed	48	77	+45	-45	CW-PG45	411-H-1213	14341	WIN-1090	ESP038732P.3	A2
Hung - Double	Pella Reserve Traditional	Aluminum Clad Wood	Vent w/ 2 Locks	Standard	Annealed	45	65	+50	-50	CW-PG50	411-H-1213	14341	WIN-1090	ESP038732P.5	A3
Hung - Double	Pella Reserve Traditional	Aluminum Clad Wood	Vent w/ 2 Locks	Standard	Annealed	41	71	+50	-50	CW-PG50	411-H-1213	14341	WIN-1090	ESP038732P.6	A3
Hung - Double	Pella Reserve Traditional	Aluminum Clad Wood	Vent w/ 2 Locks	Standard	Annealed	37	77	+50	-50	CW-PG50	411-H-1213	14341	WIN-1090	ESP038732P.7	A3
Hung - Double	Pella Reserve Traditional	Aluminum Clad Wood	Vent w/ 2 Locks	Standard	Annealed	48	59	+50	-50	CW-PG50	411-H-1213	14341	WIN-1090	ESP038732P.4	A3
Hung - Double - Precision Fit	Pella Reserve Traditional	Aluminum Clad Wood	Vent w/ 2 Locks	Standard	Annealed	48	84.735	+40	-40	CW-PG40	411-H-1219	14343	WIN-1089	ESP038732P.12	A2
Hung - Double - Precision Fit	Pella Reserve Traditional	Aluminum Clad Wood	Vent w/ 2 Locks	Standard	Annealed	41.5	72.234	+50	-50	CW-PG50	411-H-1219	14343	WIN-1089	ESP038732P.13	A2
Monumental Hung - Double	Pella Reserve Traditional	Aluminum Clad Wood	Vent w/ 2 Locks	Standard	Annealed	54	96	+50	-50	CW-PG50	411-H-1478	17769.2	NA	ESP018981P.1	A3
Monumental Hung - Double	Pella Reserve Traditional	Aluminum Clad Wood	Vent w/ 2 Locks	Standard	Annealed	72	144	+25	-25	LC-PG25	411-H-1478	NA	NA	ESP018981P.5	A3
Monumental Hung - Double	Pella Reserve Traditional	Aluminum Clad Wood	Vent w/ 2 Locks	Standard	Annealed	60	120	+30	-30	CW-PG30	411-H-1478	NA	NA	ESP018981P.4	A3
Patio Door - In-Swing	Pella Reserve Traditional and Contemporary	Aluminum Clad Wood	AP or PA	Standard	Tempered	75	95.5	+55	-70	LC-PG55	411-H-1164	14293	FL14293	ESP033751P.7	A2
Patio Door - In-Swing	Pella Reserve Traditional and Contemporary	Aluminum Clad Wood	AP or PA	Standard	Tempered	75	119.5	+40	-40	LC-PG40	411-H-1164	14293	FL14293	ESP033751P.3	A2



Test Report Information
Pella® Reserve™ Traditional
and Contemporary

Note: These charts are to be used for documentation of independent testing compliance of published Performance Class & Grade shown in the Design and Performance data tables. Use test report information where the unit width and height in the table below are equal or greater in size to the unit being specified. Contact your local Pella sales representative for copies of full test reports.

(1) Maximum performance for single units when glazed with the appropriate glass.

Product Type	Brand	Frame	Configuration	Performance Type	Glazing	Width	Height	Positive Design Pressure	Negative Design Pressure	Performance Class & Grade ¹	Hallmark Certified	FPAS# (Florida Product Approval System)	TDI# (Texas Department of Insurance)	Test Report# (Independent Report)	Canadian Performance (Pella CSA Rating Claim)
Patio Door - In-Swing	Pella Reserve Traditional and Contemporary	Aluminum Clad Wood	Fixed	Standard	Tempered	37.875	119.5	+55	-70	LC-PG55	411-H-1164	14293	FL14293	ESP033751P.4	Fixed
Patio Door - In-Swing	Pella Reserve Traditional and Contemporary	Aluminum Clad Wood	AF or FA	Standard	Tempered	75	95.5	+55	-55	LC-PG55	411-H-1436	14293	FL14293	ESP033751P.8	A3
Patio Door - Out-Swing	Pella Reserve Traditional and Contemporary	Aluminum Clad Wood	AP or PA	Standard	Tempered	75	119.5	+50	-50	LC-PG50	411-H-1188	14302	FL14302	ESP033751P.2	A3
Patio Door - Out-Swing	Pella Reserve Traditional and Contemporary	Aluminum Clad Wood	AP or PA	Standard	Tempered	75	95.5	+70	-70	LC-PG70	411-H-1188	14302	FL14302	ESP033751P.6	A3
Patio Door - Out-Swing	Pella Reserve Traditional and Contemporary	Aluminum Clad Wood	Fixed	Standard	Tempered	37.875	119.5	+50	-50	LC-PG50	411-H-1188	14302	FL14302	ESP033751P.1	Fixed
Patio Door - Out-Swing	Pella Reserve Traditional and Contemporary	Aluminum Clad Wood	Fixed	Standard	Tempered	37.875	95.5	+70	-70	LC-PG70	411-H-1188	14302	FL14302	ESP033751P.10	Fixed
Sliding Door	Pella Reserve Traditional and Contemporary	Aluminum Clad Wood	OX or XO	Standard	3/4" IG 4mm	71.25	81.5	+50	-50	LC-PG50	411-H-1520.02	47325	FL47325	ESP042681P.2	A2
Sliding Door	Pella Reserve Traditional and Contemporary	Aluminum Clad Wood	OX or XO	High Performance	3/4" IG 4mm	95.25	95.5	+50	-50	LC-PG50	411-H-1520.00	47325	FL47325	ESP042681P.1	A2
Sliding Door	Pella Reserve Traditional and Contemporary	Aluminum Clad Wood	OX or XO	Standard	3/4" IG 4mm	95.25	95.5	+35	-35	LC-PG35	411-H-1520.04	47325	FL47325	ESP042681P.3	A3
Sliding Door	Pella Reserve Traditional and Contemporary	Aluminum Clad Wood	OX or XO	Standard	3/4" IG 4mm	119.25	119.5	+20	-20	R-PG20	411-H-1520.06	47325	FL47325	ESP042681P.4	A3
Sliding Door	Pella Reserve Traditional and Contemporary	Aluminum Clad Wood	OX or XO	High Performance	3/4" IG 4mm	119.25	119.5	+30	-30	LC-PG30	411-H-1520.08	47325	FL47325	ESP042681P.4	A3
Sliding Door	Pella Reserve Traditional and Contemporary	Aluminum Clad Wood	OXO	Standard	3/4" IG 4mm	144.039	95.5	+35	-35	LC-PG35	411-H-1520.10	47325	FL47325	ESP042681P.6	A3



Test Report Information
Pella® Reserve™ Traditional and Contemporary

Note: These charts are to be used for documentation of independent testing compliance of published Performance Class & Grade shown in the Design and Performance data tables. Use test report information where the unit width and height in the table below are equal or greater in size to the unit being specified. Contact your local Pella sales representative for copies of full test reports.

(1) Maximum performance for single units when glazed with the appropriate glass.

Product Type	Brand	Frame	Configuration	Performance Type	Glazing	Width	Height	Positive Design Pressure	Negative Design Pressure	Performance Class & Grade ₁	Hallmark Certified	FPAS# (Florida Product Approval System)	TDI# (Texas Department of Insurance)	Test Report# (Independent Report)	Canadian Performance (Pella CSA Rating Claim)
Sliding Door	Pella Reserve Traditional and Contemporary	Aluminum Clad Wood	OXXO	Standard	3/4" IG 4mm	189.25	95.5	+35	-35	LC-PG35	411-H-1520.10	47325	FL47325	ESP042681P.6	A3
Sliding Door	Pella Reserve Traditional and Contemporary	Aluminum Clad Wood	OXO	Standard	3/4" IG 4mm	180.25	119,5	+20	-20	R-PG20	411-H-1520.12	47325	FL47325	ESP042681P.7Rev	A3
Sliding Door	Pella Reserve Traditional and Contemporary	Aluminum Clad Wood	OXXO	Standard	3/4" IG 4mm	237.25	119,5	+20	-20	R-PG20	411-H-1520.12	47325	FL47325	ESP042681P.7Rev	A3

Reference Sites

[WDMA Hallmark Certification](#)

[Florida Product Approval Site](#)

[Texas Department of Insurance Site](#)

For copies of full test reports contact your local Pella Sales Representative.