

SLIDING PATIO DOOR 2- AND 3-PANEL KNOCK-DOWN ASSEMBLY INSTRUCTIONS

Parts List:

- Head
- Jamb (x2)
- Sill
- Vent Panel
- Fixed Interlocker Panel
- Assembly Parts Bag(s)
- Astragal - OXO only
- Single Fixed Panel - OXO only

Tool List:

- Powered driver with #2 Phillips drive bit
- #2 Phillips screwdriver with 6" shaft
- Sealant gun with color matched sealant

SEE PAGE 3 FOR SAFETY INFORMATION.

BEFORE REMOVING PREVIOUSLY INSTALLED DOOR AND BEGINNING FRAME ASSEMBLY AND INSTALLATION:

Read through and understand all the assembly steps.

Confirm all the critical parts and assembly parts as shown in images below are installed in the frame members as noted. Factory installed parts are included in frame members based on product configuration ordered.






These parts are Assembly and/or Installation Critical!

If any parts are missing...





Contact your local sales representative or customer service team.


Parts list continued on next page...

Critical Part - OX,XO,OXO	Qty	Reason Critical
 Frame Gasket	4—Factory installed on each end of jamb parts.	Water seal at jamb to sill and jamb to head frame corners.
 Flexible Fin	2—Located in BAG B.	Seals top of jamb to head frame corners.
 Sill Filler	1—Factory installed on fixed panel side of sill.	Required for proper fixed panel position in the frame.
 Fixed Panel Spacer	3—Factory installed in fixed jamb (LH or RH).	Required for proper fixed panel position in the frame against the fixed jamb.
 Anchor (Sill)	1—Factory installed and attached w/ screws in the sill.	Required to secure fixed panel to frame.
 Anchor (Head)	1—Factory installed loose in the head, but not attached w/ screws.	Required to secure fixed panel to frame.
 Interlocker Cover Bushing	2—Included in assembly parts bag.	Guides interlocker cover screw.
 Interlocker Cover	2—Included in assembly parts bag.	Secures fixed panel to frame.
 Sill Track	1—Installed in the sill, must be removed for frame installation.	Required for vent panel operation.
 Lock Strike	1—Factory installed on astragal - OXO configurations.	Required for proper locking of door.
 Lock Hardware	1—Installed in the vent panel.	Required for proper locking of door.
 Handle Assembly	1—Shipped separate from door, must be installed into vent panel.	Required for proper locking of door.
 Anti-Lift Clip	2—Factory installed in the head. 2—Factory installed in astragal.	Prevents unwanted vent panel removal. Allows for proper panel alignment.
 Extruded Threshold or  Laminate Threshold (Laminate Exterior Units)	1—Factory installed in the sill.	Required in sill frame for proper operation.
 Pocket Covers (Laminate Exterior Units)	1 OXO—1 Factory Installed in the head.	Required to cover white stripe on frame.

BEFORE BEGINNING FRAME ASSEMBLY AND INSTALLATION (CONTINUED):

Critical Part - OXO Only	Qty	Reason Critical
 Astragal Anchor / End Seal	2-1 factory-installed in each end of astragal.	Required to secure astragal to frame.
 OXO Astragal	1-Shipped separately.	Required for proper locking of door.
 Extruded Astragal Cover or  Laminated Astragal Cover	1-Shipped separately.	Required to cover astragal installation screws.
 Sill Filler	1-Factory installed on fixed panel side of sill.	Required for proper fixed panel position in the frame.
 Fixed Panel Spacer	3-Factory installed in fixed jamb (LH or RH).	Required for proper fixed panel position in the frame against the fixed jamb.

Frame Gasket on both ends of each jamb. Inspect to confirm it is not torn or damaged.



If gasket is missing...



Contact your local sales representative or customer service team.

Parts and Screw Packages:

Confirm all labeled screws bags listed are present. If any screws are missing, please obtain comparable screws from your local hardware retailer. Screw packages may include extra screws.

 **Bag A** #8x2" Phillips Truss Head Screw - Frame Corner and Interlocker Cover
Label part #: 829Y0002

 **Bag B** Flexible Fin Corner Package, White
Label part #: 829Y0000

Installation screw and cap package.

 **Bag D** #8x1/2" Phillips Panhead Screw - Astragal Anchor, Interlocker Cover, White
Label part #: 829Y0003

 **Bag E** #8x2" Phillips Panhead Screw - Lock Strike, White
Label part #: 829Y0006

 **Bag F** #8x3/4" & #8x2-1/4" Phillips Panhead Screw - Astragal Lock Strike
Label part #: 829Y0012



Note: Installation screws and caps may be in more than one bag.



IMPORTANT SAFETY AND PRODUCT INFORMATION – DOORS

CAUTION: Many doors in older homes are painted with lead-based paint. Removal of old doors may disturb this paint. Proper precautions must be taken to minimize exposure to dust and debris. Consult state or local authorities and/or go to www.epa.gov/lead for more information.

 **WARNING:** To ensure safety and security and help prevent property damage, including possible damage to your window or door, close and lock windows and doors any time they are not being used for venting on a nice day, and particularly during high winds or rain.

IMPORTANT NOTICE

Because all construction must anticipate some water infiltration, it is important that the wall system be designed and constructed to properly manage moisture. The manufacturer is not responsible for claims or damages caused by anticipated and unanticipated water infiltration; deficiencies in building design; construction and maintenance; failure to install products in accordance with the manufacturers installation instructions; or the use of products in wall systems which do not allow for proper management of moisture within the wall systems. The determination of the flashing and sealing systems are the responsibility of the Buyer or User, the architect, contractor, installer, or other construction professional and are not the responsibility of the manufacturer.

Products should not be used in barrier wall systems which do not allow for proper management of moisture within the wall systems, such as barrier Exterior Insulation and Finish Systems (EIFS) (also known as synthetic stucco) or other non-water managed systems. Except in the states of California, New Mexico, Arizona, Nevada, Utah and Colorado, the manufacturer makes no warranty of any kind on and assumes no responsibility for window and doors installed into barrier wall systems. In the states listed above, the installation of products in barrier wall systems or similar systems must be in accordance with the manufacturers installation

CARE AND MAINTENANCE

Care and maintenance information is available by contacting your local retailer or customer service representative, or by visiting the manufacturer's website.

CLEANING INSTRUCTIONS

GLASS: Remove any protective film and labels and clean the glass, using a soft, clean, grit-free cloth and mild soap or detergent. Be sure to remove all liquid by wiping dry or use a clean squeegee.

VINYL DOOR FRAMES: The vinyl frame may be cleaned using the same method as the glass. For stubborn dirt, a "non-abrasive" cleaner such as Bon-Ami® or Soft Scrub® may be used. Do not use solvents such as mineral spirits, toluene, xylene, naphtha or muriatic acid as they can dull the finish, soften the vinyl and/or cause failure of the insulated unit seal. Do not use Isopropyl Alcohol on laminated surfaces as it will damage the finish. Keep door tracks clear of dirt and debris. Keep weep holes open and clear of obstructions.

DO NOT use abrasives. DO NOT scrape or use tools that might damage the surface.

NOTICE: DO NOT use inappropriate solvents or brickwash or cleaning chemicals. If you do, permanent damage can result and the product failure, loss or damage would not be covered by the Limited Warranty.

1 Frame Prep:

A. **Non-Laminate Exterior Units:** Remove the threshold and the sill track with bumper from the sill frame.

Laminate Exterior Units: Remove the threshold and the sill track with bumper from the sill frame. Remove the astragal and head pocket covers.

Threshold



Sill Track



Frame Layout and Assembly OVERVIEW:




OVERVIEW / PREVIEW ONLY. OVERVIEW / PREVIEW ONLY. OVERVIEW / PREVIEW ONLY.

Overview only, follow process steps on the following page.


Lay parts on a flat hard surface with exterior side up. Labels attached to the side of the frame parts identify each part to assist in correct part positioning prior to assembly.

TIP: Lay frame parts out with wood blocks under each corner.

Screw packages may include extra screws.





Align screws with these holes, screw holes to be covered with color-matched sealant before frame assembly.



2 Frame Assembly PROCESS:

- A. **Starting on one frame corner**, apply sealant over each of the screw holes of the head or sill.



- B. **Apply sealant to the three legs** of the matching jamb which make up the panel channels.



 **Bag A** #8x2-1/2" Phillips Truss Head Screw - Frame Corner and Interlocker Cover
V988327 Label part #: 829Y0002




- C. **Starting in one frame corner**, insert (Qty 4) screws from Bag A into the frame by driving the screws first through the jamb, (use care to not tear the jamb gasket), so they protrude on the exit side. Align each screw with the screw holes in the matching frame part. Start all 4 screws in the matching frame part (head or sill) before fully tightening the screws. Do not overtighten.

Tip: Finish tightening by hand.




NOTICE: Do Not tighten screws past a slight dimple. Overtightening the screws may damage the vinyl parts.




2 Frame Assembly PROCESS (continued):

D. Continue to work around the frame until all four corners are assembled.

Note: Extra screws may be included and may also be used in subsequent steps. Do Not throw out extra screws.





E. Clean sealant squeeze-out in each corner.



F. Add sealant to any noticeable gaps between the jamb and head or sill. Clean up excess sealant.




3 Flexible Fin Corner Install:



- A. **Nail fin product:** From Bag B, at each of the assembled top two corners of the frame, remove release paper from provided flexible fin corner and fold to install the fin corner over the installation fins, making sure the exterior corner is covered.



- B. **Block frame product:** From Bag B, at each of the assembled top two corners of the frame, remove release paper from provided flexible fin corner, and install the fin corner over the edges of the corner as shown. Trim flush with interior edge as needed.



4 Install Frame into Rough Opening:


Install the assembled door frame into the rough opening.

Installation screws and caps are included in the Parts and Screw package.




5 Sill Track Installation - OX and XO only:


- A. **Re-install the sill track with bumper into sill.** Make sure the longer outside track leg is toward the interior and the shorter leg toward the exterior. The sill track must slope toward the exterior. The bumper can be found in the assembly parts kit and goes against the frame on the fixed panel side.




For OXO units the sill track will be installed in a later step.




3-PANEL CONFIGURATIONS (as viewed from the exterior):



Panel Identifying Tips:




Fixed Interlocker Panel - has exterior weatherstrip on only three panel edges.



Single Fixed Panel - has weatherstrip around the exterior perimeter of the panel.

6 Fixed Interlocker Panel Installation PROCESS:

A. **Confirm the head anchor** (located in the head) is slid to the vent side, so as not to interfere fixed panel installation.



B. **Confirm all three panel spacers are installed** in the jamb (top, middle & bottom).





If the panel spacers are missing when the fixed interlocker panel is installed, the door will likely not lock.

DO NOT install panel, contact your local sales representative or customer service team.



Panel Spacer




C. **From the exterior**, lift the fixed interlocker panel up and insert the top of the panel into the exterior head track. Make sure the panel is positioned so the weep holes on the exterior glazing beads at the bottom of the panel.

D. **Slide the bottom** of the panel into a vertical position.

E. **Place the panel bottom** into the exterior sill pocket.

Note: The fixed interlocker panel does NOT get installed over the sill roller track.



6 Fixed Interlocker Panel Installation PROCESS (continued):


Bag D
#8x1/2" Phillips Panhead Screw - Astragal Anchor, Interlocker Cover, White
V988328
Label part #: 829Y0003



- F. Slide the head anchor above the edge of the fixed interlocker panel and align the screw holes with the pre-drilled holes in the frame head. Install and tighten, by hand (Qty 2) - #8 x 1/2" painted pan head screws from Bag D.



Interlocker Cover Installation OVERVIEW:

OVERVIEW / PREVIEW ONLY. OVERVIEW / PREVIEW ONLY. OVERVIEW / PREVIEW ONLY. OVERVIEW / PREVIEW ONLY. OVERVIEW / PREVIEW ONLY.

Overview only, follow process steps below.




Install short screw first.

Insert Interlocker Cover Bushing into Interlocker Cover.


Install 2-1/2" screw through Interlocker Cover through bushing.

Bushing in accessory bag; only screws are in the numbered accessory bags.


	Bag A	#8x2" Phillips Truss Head Screw - Frame Corner and Interlocker Cover Label part #: 829Y0002
	Bag D	#8x1/2" Phillips Panhead Screw - Astragal Anchor, Interlocker Cover, White Label part #: 829Y0003




XO Interior View




OX Interior View



OXO Vent Left – Interior View



OXO Vent Right – Interior View



7 Interlocker Cover Installation PROCESS:

A. Position the fixed interlocker cover in the cut-out at the top edge of the fixed panel with the angle screw hole at the top.



B. Insert from Bag D (Qty 1) #8 x 1/2" into the bottom screw hole. Finish tightening the screw by hand.

 **Bag D** #8x1/2" Phillips Panhead Screw - Astragal Anchor, Interlocker Cover, White
V988328 Label part #: 829Y0003



C. Insert Interlocker Cover Bushing into the interlocker cover before installing the 2-1/2" screw.



D. Complete the interlocker cover attachment by inserting the Bag A (Qty 1) 8 x 2 -1/2" screw in the top cover hole toward the rough opening and finish tightening by hand.

 **Bag A** #8x2" Phillips Truss Head Screw - Frame Corner and Interlocker Cover
V988327 Label part #: 829Y0002




7 Interlocker Cover Installation PROCESS (continued):

Repeat 7A - 7D on the lower interlocker cover, flipping the cover vertically. For the lower interlocker cover, be sure to install the 1/2" screw in the top hole first and the bushing and the 2-1/2" screw in the bottom hole second.




Astragal Installation OVERVIEW - OXO


Overview only, follow process steps below.



OXO Vent Left – Interior View



OXO Vent Right – Interior View



OVERVIEW / PREVIEW ONLY.

8 Astragal Installation PROCESS - OXO:

- A. Remove the astragal cover.
- B. Remove the tape from the astragal anchor from each end of the astragal.
- C. Position the astragal in the frame with the anchors in exterior fixed track.
- D. Position the astragal against the fixed panel.




- E. Install the #8 x 2-1/4" screw from Bag F through the astragal into the fixed panel at each pre-drilled hole.




Note: Astragal attachment screws are not color matched.

OXO Vent Left – Interior View




OXO Vent Right – Interior View



8 Astragal Installation PROCESS - OXO (continued):

- F. Insert and tighten Bag D (Qty 2) - #8 x 1/2" painted pan head astragal anchor screws at the sill and the head.



Head View



Sill View

9 Astragal Cover Installation - OXO:

- A. Align and insert one end of the astragal cover in the open astragal pocket and continue to position the cover in the pocket along the length of the astragal.



Extruded astragal cover shown, will be a different color on laminated units.

- B. Press the cover along the length of the astragal to make sure it is fully seated in the pocket.



10 Threshold Cover Installation:

- A. **Install the threshold cover.** Insert the threshold cover end into the exterior sill track and press down into place.

Laminate Exterior Units: First install sill threshold, followed by the head pocket cover.




11 Sill Filler Installation - OXO:

- A. **Insert the filler end into the sill track, OXO only,** and press down along the length of the filler to fully in into the sill.



12 Sill Track Installation - OXO:

- A. Re-install the sill track with bumper into sill. Make sure the longer outside track leg is toward the interior and the shorter leg toward the exterior. The sill track must slope toward the exterior. The bumper goes against the frame on the fixed panel side. Push down until the track "snaps" into position.



13 Vent Panel Installation:

- A. Slide the anti-lift clip(s) in the head out of the way before installing the vent panel.


Note: The panel rollers are fully retracted to facilitate panel installment.

- B. Insert the top of the vent panel into the interior head track and slide the bottom of the panel into vertical alignment, making sure the rollers are aligned with the sill roller track.



13 Vent Panel Installation (continued):

C. Use a #2 Phillips screwdriver with a 6" shaft to adjust rollers on each side of the panel to ensure smooth operation and even reveal between the panel and frame jamb along the length of the panel. Adjust rollers to raise panel far enough so it is not dragging on the sill. Turn the screwdriver to the clockwise to raise the panel and counter-clockwise to lower the panel.



Rollers must be adjusted prior to adjusting the lock strike.

D. Slide the anti-lift clips to above the "closed" vent panel position.



14 Panel Handle Hardware Installation - OXO:

A. Use the installation instructions included with the hardware.


15 Lock Strike Adjustment - XO/OX:

A. **Adjust the lock strike on the frame lock jamb**, so it aligns with the lock. Lock strike comes attached with screws in the slotted adjustment holes. Loosen these screws to adjust strike up or down to align with vent panel lock. Tighten screws when alignment is complete.

Note: the two separate photos below are positioned for alignment demonstration purposes.



Loosen screws in the slotted holes and adjust strike to align with lock up or down as needed.



B. **After adjustment;** finish installing with Qty (4) - #8 x 2" painted pan head screws.




V988332

Bag
E

#8x2" Phillips Panhead Screw - Lock Strike, White

Label part #: 829Y0006



15 Lock Strike Adjustment - OXO (continued):


C. **Adjust the lock strike on the frame lock jamb**, so it aligns with the lock. Lock strike comes attached with screws in the slotted adjustment holes. Loosen these screws to adjust strike up or down to align with vent panel lock. Tighten screws when alignment is complete.



Loosen screws in the slotted holes and adjust strike to align with lock up or down as needed.

OXO Lock Strike

Note: the two separate photos below are positioned for alignment demonstration purposes.



D. **After adjustment;**

OXO - Finish installing the strike into the jamb with Qty (4) - #8 x 3/4" pan head screws from Bag F.

	Bag F	#8x3/4" & #8x2-1/4" Phillips Panhead Screw - Astragal Lock Strike
V988338		Label part #: 829Y0012



Note: OXO Astragal lock strike screws are not color matched.



OXO Lock Strike